# SAFETY DATA SHEET



Revision date: 14-May-2020

**Revision Number** 1

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product identifier** 

Product Name Civilox - HB200 Light Grey Part A

**Product Code(s)** 000000067003

Other means of identification

UN number 3082

Synonyms SDS003/01

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Coating for concrete and steel.

**Uses advised against** No information available.

Supplier

Liquimix Pty Ltd ABN: 32 062 887 585 Street Address: 24 Rosa Place Richlands QLD 4077

Australia

Telephone Number: +61 7 3277 6655

#### Emergency telephone number

Emergency telephone number 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

# 2. HAZARDS IDENTIFICATION

### **GHS Classification**

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to the provisions of the Australian Code for the Transport of Dangerous Goods by Road and Rail when transported by road or rail in: packagings that do not incorporate a receptacle exceeding 500 kg(L); or IBCs.

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

| Skin corrosion/irritation         | Category 2  |
|-----------------------------------|-------------|
| Serious eye damage/eye irritation | Category 2A |

| Skin sensitization       | Category 1 |
|--------------------------|------------|
| Acute aquatic toxicity   | Category 2 |
| Chronic aquatic toxicity | Category 2 |

#### SIGNAL WORD

Danger

#### Label elements

Environment Exclamation mark





#### **Hazard statements**

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations: H411 - Toxic to aquatic life with long lasting effects

#### **Precautionary Statements - Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash hands thoroughly after handling

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves/protective clothing/eye protection/face protection

Avoid release to the environment

# **Precautionary Statements - Response**

Specific treatment (see First aid on this SDS)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eve irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Avoid breathing vapour or spray mist.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Collect spillage

# **Precautionary Statements - Storage**

No storage statements.

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Other hazards which do not result in classification

Poisons Schedule (SUSMP) None allocated

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Substance

Not applicable

### Mixture

| Chemical name                        | CAS No.    | Weight-% |
|--------------------------------------|------------|----------|
| Bisphenol A, epichlorohydrin polymer | 25068-38-6 | 30-60    |
| Talc                                 | 14807-96-6 | 10-<30   |
| Phenol, methylstyrenated             | 68512-30-1 | 5-<20    |
| Alkyl (C12-14) glycidyl ether        | 68609-97-2 | 1-10     |
| Titanium dioxide                     | 13463-67-7 | 1-10     |
| Other component(s)                   | -          | to 100   |

# 4. FIRST AID MEASURES

### **Description of first aid measures**

General advice For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New

Zealand 0800 764 766) or a doctor.

**Emergency telephone number** Poisons Information Center, Australia: 13 11 26

Poisons Information Center, New Zealand: 0800 764 766

Inhalation Remove to fresh air and keep at rest in a position comfortable for breathing. (Call a

physician if symptoms occur).

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes.

**Ingestion** Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. See section 8 for more information. Avoid

contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

**Symptoms** May cause allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

# 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media** 

Suitable Extinguishing Media Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal

protein foam can be used.

Unsuitable extinguishing media

Specific hazards arising from the chemical

Specific hazards arising from the

chemical

In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Revision Number 1

**Hazardous combustion products** Carbon oxides. Hydrogen chloride.

Special protective actions for fire-fighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

Revision date: 14-May-2020

gear. Use personal protection equipment.

Hazchem code •3Z

# 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Do not touch or walk through

spilled material.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

**Environmental precautions** 

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dike far

ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal.

Methods for cleaning up

Use a non-combustible material like vermiculite, sand or earth to soak up the product and

place into a container for later disposal.

# 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Use according to

package label instructions. Handle in accordance with good industrial hygiene and safety

practice. Avoid contact with skin, eyes or clothing.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container

closed when not in use.

Classified as a C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and

transport requirements.

**Incompatible materials** Strong oxidizing agents.

Poisons Schedule (SUSMP) None allocated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

**Exposure Limits** 

. No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

| Chemical name                  | Australia     | ACGIH TLV                                                                                                        |
|--------------------------------|---------------|------------------------------------------------------------------------------------------------------------------|
| Talc<br>14807-96-6             | 2.5 mg/m³ TWA | TWA: 2 mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter |
| Titanium dioxide<br>13463-67-7 | 10 mg/m³ TWA  | TWA: 10 mg/m <sup>3</sup>                                                                                        |

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

#### **Appropriate engineering controls**

# **Engineering controls**

Apply technical measures to comply with the occupational exposure limits.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

## Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.









Eye/face protection

Goggles.

Skin and body protection

Wear suitable protective clothing. Boots. Overalls.

Hand protection Wear suitable gloves. Impervious gloves.

If determined by a risk assessment an inhalation risk exists, wear an organic vapour Respiratory protection

respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

No information available. **Environmental exposure controls** 

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

**Appearance** No information available. Color Light grey and other colors

Odor Aromatic.

**Odor threshold** No information available.

Property Values Remarks • Method

No data available Ha None known

Melting point / freezing point No data available Boiling point / boiling range No data available

Flash point >94 None known None known **Evaporation rate** No data available None known Flammability (solid, gas) No data available Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapor pressure No data available Vapor density No data available

Relative density 1.30

Water solubility Immiscible in water

Solubility(ies) No data available None known **Partition coefficient** No data available None known

**Autoignition temperature** No data available

**Decomposition temperature** None known No data available Kinematic viscosity No data available None known **Dynamic viscosity** No data available None known

Other information

# 10. STABILITY AND REACTIVITY

Reactivity

Reactivity No information available.

**Chemical stability** 

Stable under normal conditions. Stability

**Explosion data** 

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Possibility of hazardous reactions

Revision Number 1

Possibility of hazardous reactions None under normal processing.

**Conditions to avoid** 

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition products** 

Hazardous decomposition products Carbon oxides. Hydrogen chloride.

# 11. TOXICOLOGICAL INFORMATION

## **Acute toxicity**

### Information on likely routes of exposure

**Product Information** . No adverse health effects expected if the chemical is handled in accordance with this

Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the

Revision date: 14-May-2020

chemical is mishandled and overexposure occurs are:.

**Inhalation** May cause irritation.

**Eye contact** Causes serious eye irritation.

**Skin contact** Irritating to skin. May cause sensitization by skin contact.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

**Symptoms** May cause redness and tearing of the eyes.

### Numerical measures of toxicity - Product Information

No information available.

The following values are calculated based on chapter 3.1 of the GHS document

**Component Information** 

| Chemical name                        | Oral LD50           | Dermal LD50           | Inhalation LC50 |
|--------------------------------------|---------------------|-----------------------|-----------------|
| Bisphenol A, epichlorohydrin polymer | = 11400 mg/kg (Rat) | •                     | -               |
| Alkyl (C12-14) glycidyl ether        | = 17100 mg/kg (Rat) | > 3987 mg/kg (Rabbit) | -               |
| Titanium dioxide                     | > 10000 mg/kg (Rat) | -                     | -               |

See section 16 for terms and abbreviations

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Irritating to skin. Classification is based on mixture calculation methods based on

component data.

Serious eye damage/eye irritation Causes serious eye irritation. Classification is based on mixture calculation methods based

on component data.

Respiratory or skin sensitization May cause sensitization by skin contact. Classification is based on mixture calculation

methods based on component data.

Germ cell mutagenicity No information available.

**Carcinogenicity** No information available.

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Aspiration hazard** No information available.

Chronic effects: Talc (not containing asbestos or asbestiform fibres) has been classified by the International

Agency for Research on Cancer (IARC) as a Group 3 agent. The agent is not classifiable

as to its carcinogenicity to humans.

Titanium dioxide has been classified by the International Agency for Research on Cancer

(IARC) as a Group 2B agent. The agent is possibly carcinogenic to humans.

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

**Ecotoxicity** 

. Keep out of waterways. Toxic to aquatic life with long lasting effects.

| Chemical name | Algae/aquatic plants | Fish                                      | Toxicity to microorganisms | Crustacea |
|---------------|----------------------|-------------------------------------------|----------------------------|-----------|
| Talc          | -                    | LC50: >100g/L (96h,<br>Brachydanio rerio) | -                          | -         |

# Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

**Bioaccumulation** No information available.

**Component Information** 

**Mobility** 

Mobility in soil No information available.

Other adverse effects

| Chemical name                | EU - Endocrine Disrupters | EU - Endocrine Disruptors - | Endocrine disrupting potential |
|------------------------------|---------------------------|-----------------------------|--------------------------------|
|                              | Candidate List            | Evaluated Substances        |                                |
| Bisphenol A, epichlorohydrin | Group III Chemical        | -                           | -                              |
| polymer                      |                           |                             |                                |

# 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Waste from residues/unused products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of weld

containers.

# 14. TRANSPORT INFORMATION

#### **ADG**

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and

Rail; DANGEROUS GOODS.

UN number 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS

BISPHENOL A, EPICHLOROHYDRIN POLYMER)

Hazard class 9
Packing group III
Hazchem code •3Z

#### **IATA**

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN number 3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS

BISPHENOL A, EPICHLOROHYDRIN POLYMER)

Transport hazard class(es) 9
Packing group III

#### **IMDG**

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN number 3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS

BISPHENOL A, EPICHLOROHYDRIN POLYMER)

Transport hazard class(es)

Packing group

IMDG EMS Fire

F-A

IMDG EMS Spill

S-F

Marine pollutant

Yes

# 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

# **National regulations**

#### Australia

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to the provisions of the Australian Code for the Transport of Dangerous Goods by Road and Rail when transported by road or rail in: packagings that do not incorporate a receptacle exceeding 500 kg(L); or IBCs.

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

Poisons Schedule (SUSMP) None allocated

**International Inventories** 

All the constituents of this material are listed on the Australian Inventory of Chemical **AICS** 

Substances.

Legend:

AICS - Australian Inventory of Chemical Substances

**International Regulations** 

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

# 16. OTHER INFORMATION

Reason(s) For Issue: First Issue Primary SDS

**Issuing Date:** 14-May-2020

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

### **Revision Note:**

The symbol (\*) in the margin of this SDS indicates that this line has been revised.

## Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value Skin designation

Carcinogen

# Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

RTECS (Registry of Toxic Effects of Chemical Substances)

World Health Organization

Disclaimer

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Liquimix Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Liquimix representative or Liquimix Pty Ltd at the contact details on page 1.

Liquimix Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

**End of Safety Data Sheet**