

LM WireTrim Tape

Edge Cutting Tape

PRODUCT

DESCRIPTION

A narrow, flexible adhesive tape allowing for sharp, professional looking edges.

INTENDED

USES

- Professional looking edges when using Spray applied membranes
- Cutting coatings in automobile spray applications

FEATURES

- Enables sharp, precise cuts through tough polyurea and polyurethane coatings
- High-tack, co-polymer adhesive that sticks instantly, allowing for unlimited repositioning
- Conforms well to compound curves and tight corners

PRODUCT DATA

| Size | 6mm x 30m |
|------------------------|------------|
| Material | PET |
| Release Paper Liner | 80g |
| PET d/s Tape Thickness | 250 μm |
| Wire Diameter | 0.25mm |
| Peel Adhesion | >14 N/25mm |
| Initial Adhesion | <180mm |
| Temperature Resistance | 80°C |

APPLICATION

- 1 Cut tape away, creating a wire that sticks up and can later be pulled
- 2 Position the tape with the wire edge facing the area to be sprayed
- 2 Spray Polyurethane / Polyurea coating
- 3 Pull the wire filament out and through the coating to achieve sharp, professional edges

STORAGE & HANDLING

Store in dry, shaded conditions away from sources of heat. Protect from heat and frost. Protect from moisture.

TAPE SIZE

6mm x 30m

DISCLAIMER

The information contained herein is offered without charge and is for use by technically qualified personnel at their own risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and no warranty of any kind is made with respect thereto.

LiquiMix Pty Ltd - ABN 32 062 887 585 24 Rosa Place, Richlands QLD 4077

Phone: 1300 123 085

Web: - <u>www.liquimix.com</u>
Sales Enquiries: - <u>sales@liquimix.com</u>
Account Enquiries: - <u>accounts@liquimix.com</u>