

Thinner LM5 Slow

Retarder Paint Thinner

PRODUCT

DESCRIPTION Thinner used to reduce viscosity for application of Liquimix coatings where this thinner is listed on the technical datasheet. Can be used to increase the tack time (wet time) when brushing or rolling large areas.

INTENDED

USES

- Slow thinner for Liquimix coatings
- Improves brushing and rolling properties
- Improves application of coatings in windy and warm conditions

PRODUCT DATA

Volume Solids	0%
Colour	Colourless
Flash Point	58 °C
VOC	949 Grams/Litre
Specific Gravity	0.95

Mixing

Not required

Thinning

Thin by adding Thinner LM5 under stirring to the paint at up to the desired amount. Take care not to exceed the limit as specified on the appropriate Technical Datasheet (TDS) as published on the Liquimix website.

STORAGE & HANDLING

Store in dry, shaded conditions away from sources of heat and ignition and in properly sealed containers. Protect from heat and frost. Protect contents from moisture. A shelf life of 12 months minimum is typical with unopened containers if stored at ambient conditions at 25°C. If either component is opened and partially used, it should be purged with nitrogen or desiccated air and resealed.

PACK SIZE

4L Pail
20L Pail

HEALTH & SAFETY

Thinner LM5 is a dangerous good and hazardous. Thinner LM5 is flammable. Thinner LM5 is for professional use only. This product should not be used without consulting the Safety Datasheet (SDS) as published on the Liquimix website first. Observe all health and safety as well as environmental legislation.

DISCLAIMER

The information contained herein is offered without charge and is for use by technically qualified personnel at their own risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and no warranty of any kind is made with respect thereto.