

SAFETY DATA SHEET



Revision date: 07-Oct-2024

Revision Number 1

Section 1: Identification

Product identifier

Product Name PU-40 Polyurethane Clear Part B

Product Code(s) 000000067026

Other means of identification

UN number or ID number 1307

Safety data sheet number PU069

Recommended use of the chemical and restrictions on use

Recommended use Coating for concrete.

Uses advised against No information available.

Details of manufacturer or importer

Supplier

Liquimix Pty Ltd
ABN: 32 062 887 585
Street Address: 24 Rosa Place
Richlands QLD 4077
Australia

Telephone Number: +61 7 3277 6655

Emergency telephone number

Emergency telephone number **1 800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

Section 2: Hazard identification

Classified as a hazardous substance in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).
Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

GHS Classification

Flammable liquids	Category 3
Aspiration hazard	Category 1
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3

Label elements

Flame

Exclamation mark



Signal word
DANGER

Hazard statements

H226 - Flammable liquid and vapor
 H312 + H332 - Harmful in contact with skin or if inhaled
 H335 - May cause respiratory irritation
 H315 - Causes skin irritation
 H304 - May be fatal if swallowed and enters airways
 H317 - May cause an allergic skin reaction
 Repeated exposure may cause skin dryness or cracking

Precautionary Statements - Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Keep container tightly closed.
 Ground and bond container and receiving equipment.
 Use explosion-proof electrical/ ventilating / lighting/ .? / equipment.
 Use non-sparking tools.
 Take action to prevent static discharges.
 Wear protective gloves/clothing and eye/face protection.
 Avoid breathing dust/fume/gas/mist/vapors/spray.
 Use only outdoors or in a well-ventilated area.
 Wash face, hands and any exposed skin thoroughly after handling.
 Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements - Response

Specific treatment (see First aid on this SDS).
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 Call a POISON CENTER or doctor/physician if you feel unwell.
 If skin irritation or rash occurs: Get medical advice/attention.
 Take off contaminated clothing and wash before reuse.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER or doctor if you feel unwell.
 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
 Do NOT induce vomiting.
 In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet to extinguish..

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool.
 Store locked up.

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Other hazards which do not result in classification**Section 3: Composition and information on ingredients**

Chemical name	CAS No.	Weight-%
Xylene	1330-20-7	50-60%
Hexamethylene diisocyanate, homopolymer	28182-81-2	40-50%

Section 4: First aid measures**Description of first aid measures**

Inhalation	Remove to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, (trained personnel should) give oxygen. Give artificial respiration if victim is not breathing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Seek immediate medical attention/advice. Aspiration into lungs can produce severe lung damage.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin contact	Remove and isolate contaminated clothing and shoes. Wash off immediately with soap and plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
Ingestion	Rinse mouth thoroughly with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Get immediate medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms May cause allergic skin reaction.

Effects of Exposure No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically. Aspiration may cause pulmonary edema and pneumonitis.

Section 5: Firefighting measures**Suitable Extinguishing Media**

Suitable extinguishing media Dry chemical, CO2, sand, earth, water spray or regular foam.

Unsuitable extinguishing media Water.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Flammable. Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixture with air. Vapors may travel to source of ignition and flash back. Flash back possible over considerable distance. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Containers may explode when heated. Cool drums with water spray.

Hazardous combustion products Carbon oxides.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code 3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. All equipment used when handling the product must be grounded. Avoid breathing vapors or mists. Ensure adequate ventilation. Wear protective gloves/clothing and eye/face protection.

For emergency responders Pay attention to flashback. Remove all sources of ignition. Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

Methods for cleaning up Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers.

Section 7: Handling and storage**Precautions for safe handling**

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

General hygiene considerations Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Do not eat, drink or smoke when using this product. Wear suitable gloves and eye/face protection. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Store locked up.

This material is a Scheduled Poison and must be stored, maintained and used in accordance with the relevant regulations.

Incompatible materials Strong oxidizing agents. Strong acids.

Section 8: Exposure controls and personal protection**Control parameters**

Exposure Limits No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Chemical name	Australia	New Zealand	ACGIH TLV
Xylene 1330-20-7	TWA: 80 ppm TWA: 350 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	TWA: 50 ppm TWA: 217 mg/m ³	TWA: 20 ppm

Chemical name	European Union	United Kingdom	Germany DFG
---------------	----------------	----------------	-------------

Xylene 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ *	TWA: 50 ppm TWA: 220 mg/m ³ STEL: 100 ppm STEL: 441 mg/m ³ Sk*	TWA: 50 ppm TWA: 220 mg/m ³ Peak: 100 ppm Peak: 440 mg/m ³ Sk*
Chemical name	Australia	ACGIH	European Union
Xylene 1330-20-7	-	1.5 g/g creatinine	-

Isocyanates, all (as -NCO): 8hr TWA = 0.02 mg/m³, 15 min STEL = 0.07 mg/m³, Sen

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL - (ACGIH - Short-Term Exposure Limit) - a 15-minute TWA exposure which should not be exceeded at any time during a work day even if the 8-hour TWA is within the ACGIH -TWA. Exposures above the ACGIH-TWA up to the STEL should not be longer than 15 minutes and should not occur more than four times per day. There should be at least 60 minutes between successive exposures in this range.

`Sk' (skin) Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

`Sen' Notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance and should not be further exposed to the substance.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls

Engineering controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.



Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear suitable protective clothing.

Hand protection Impervious gloves.

Respiratory protection If determined by a risk assessment an inhalation risk exists, wear an organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Environmental exposure controls No information available.

Thermal hazards No information available.

Section 9: Physical and chemical properties**Information on basic physical and chemical properties**

Physical state	Liquid
Appearance	Clear
Color	Colourless
Odor	Aromatic
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash point	26°C	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	0.8 - 1.2 kPa	None known
Vapor density	No data available	None known
Relative density	0.96	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	432°C --530°C	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information**Section 10: Stability and reactivity****Reactivity**

Reactivity Reacts with strong oxidising agents.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials Strong oxidizing agents. Strong acids.

Hazardous decomposition products

Hazardous decomposition products Carbon oxides.

Section 11: Toxicological information**Information on likely routes of exposure**

Product Information No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:

Inhalation Inhalation of vapors in high concentration may cause irritation of respiratory system. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

Eye contact May cause irritation.

Skin contact Causes skin irritation. May cause sensitization by skin contact. Prolonged skin contact may defat the skin and produce dermatitis.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause central nervous system depression. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Symptoms Asthma-like and/ or skin allergy-like symptoms. Vapors may cause drowsiness and dizziness.

Acute toxicity**Numerical measures of toxicity - Product Information**

No information available

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Hexamethylene diisocyanate, homopolymer	= >2500 mg/kg (Female Rat)	= >2000 mg/kg (Rat)	= 18500 mg/m ³ (Rat) 1 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Mild eye irritation.

Respiratory or skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No information available.

Carcinogenicity Not expected to be carcinogenic. Contains a known or suspected carcinogen.

Chemical name	Australia	European Union	IARC
Xylene - 1330-20-7	-	-	Group 3

IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity No information available.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure No information available.

Aspiration hazard May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity Keep out of waterways.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Xylene	-	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)

Terrestrial ecotoxicity There is no data for this product.

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Xylene	3.15

Mobility

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Dispose of contents/containers in accordance with local regulations.

See section 8 for more information

Section 14: Transport information

ADG Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

UN number or ID number 1307
Proper shipping name FLAMMABLE LIQUID, N.O.S. (CONTAINS XYLENE)
Transport hazard class(es) 3
Packing group III
Hazchem code 3Y

IATA Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN number 1307
UN proper shipping name FLAMMABLE LIQUID, N.O.S. (CONTAINS XYLENE)
Transport hazard class(es) 3
Packing group III

IMDG Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN number 1307
UN proper shipping name FLAMMABLE LIQUID, N.O.S. (CONTAINS XYLENE)
Transport hazard class(es) 3
Packing group III

IMDG EMS Fire F-E
IMDG EMS Spill S-D

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

Classified as a hazardous substance in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).
Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number 6

Australian Industrial Chemicals Introduction Scheme (AICIS)

-

Chemical name	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Xylene - 1330-20-7	Present	-
Hexamethylene diisocyanate, homopolymer - 28182-81-2	Present	-

Illicit Drug Precursors/Reagents

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Xylene - 1330-20-7	10 tonne/yr Threshold category 1 including individual or mixed isomers

International Inventories

AIIC

All the constituents of this material are listed on the Australian Inventory of Industrial Chemicals.

NZIoC

Contact supplier for inventory compliance status.

TSCA

Contact supplier for inventory compliance status.

DSL/NDSL

Contact supplier for inventory compliance status.

EINECS/ELINCS

Contact supplier for inventory compliance status.

ENCS

Contact supplier for inventory compliance status.

IECSC

Contact supplier for inventory compliance status.

KECL Contact supplier for inventory compliance status.
PICCS Contact supplier for inventory compliance status.

Legend:**AIIC- Australian Inventory of Industrial Chemicals****NZIoC - New Zealand Inventory of Chemicals****TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS** - Japan Existing and New Chemical Substances**IECSC** - China Inventory of Existing Chemical Substances**KECL** - Korean Existing and Evaluated Chemical Substances**PICCS** - Philippines Inventory of Chemicals and Chemical Substances**International Regulations****The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable**The Stockholm Convention on Persistent Organic Pollutants** Not applicable**The Rotterdam Convention** Not applicable**Section 16: Other information**

Supplier Safety Data Sheet

Reason(s) For Issue: First Issue Primary SDS**Prepared By** This Safety Data Sheet has been prepared by IXOM Operations Pty Ltd (Toxicology and SDS Services).**Revision date:** 07-Oct-2024**Revision Note:**

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend**

SVHC: Substances of Very High Concern for Authorization:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate

LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGl(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
Australian Industrial Chemicals Introduction Scheme (AICIS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Disclaimer

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Liquimix Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Liquimix representative or Liquimix Pty Ltd at the contact details on page 1.

Liquimix Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

End of Safety Data Sheet