

SAFETY DATA SHEET

Revision date: 25-Nov-2024

Revision Number 2

Section 1: Identification

Product identifier

Product Name Civilox - HB200 Part B

Product Code(s) 000000067004

Other means of identification

Recommended use of the chemical and restrictions on use

Recommended use Concrete sealer.

Uses advised against No information available.

Details of manufacturer or importer

Supplier

Liquimix Pty Ltd
ABN: 32 062 887 585
Street Address: 24 Rosa Place
Richlands QLD 4077
Australia

Telephone Number: +61 7 3277 6655

*Emergency telephone number

Emergency telephone number **1800 638 556 (24 HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

Section 2: Hazard identification

Classified as a hazardous substance in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).
Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

GHS Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1

Label elements

Corrosion
Exclamation mark



Signal word

DANGER

Hazard statements

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves/clothing and eye/face protection.

Wash hands thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Precautionary Statements - Response

Specific treatment (see First aid on this SDS).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Precautionary Statements - Storage

No storage statements.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Other hazards which do not result in classification**Section 3: Composition and information on ingredients**

Chemical name	CAS No.	Weight-%
Talc	14807-96-6	30 - 60%
Cashew nutshell liquid	8007-24-7	10 - 40%
Benzyl alcohol	100-51-6	10 - 30%
m-Xylene a,a"-diamine	1477-55-0	< 2%
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures**Description of first aid measures****General advice**

For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor.

Inhalation

Remove to fresh air and keep at rest in a position comfortable for breathing. Medical aid is necessary if symptoms appear to be an obvious consequence of inhalation.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Immediate medical attention is required.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. In the case of skin irritation or allergic reactions see a physician.

Ingestion

Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms May cause allergic skin reaction.

Effects of Exposure No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically. Can cause corneal burns.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable extinguishing media Dry chemical, CO₂, water spray or regular foam.

Unsuitable extinguishing media

Specific hazards arising from the chemical

Specific hazards arising from the chemical In the event of fire, cool tanks with water spray.

Hazardous combustion products Carbon oxides. Oxides of silicon. Oxides of magnesium. Nitrogen oxides.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal.

Methods for cleaning up

Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Section 7: Handling and storage**Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Avoid breathing vapors or mists. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use.

Classified as a C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

Incompatible materials

Strong oxidizing agents. Strong acids.

Section 8: Exposure controls and personal protection**Control parameters****Exposure Limits**

No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Chemical name	Australia	New Zealand	ACGIH TLV
Talc 14807-96-6	TWA: 2.5 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter
m-Xylene a,a"-diamine 1477-55-0	Peak: 0.1 mg/m ³	Sk* Ceiling: 0.1 mg/m ³	Sk* Ceiling: 0.018 ppm

Chemical name	European Union	United Kingdom	Germany DFG
Talc 14807-96-6	-	TWA: 1 mg/m ³ STEL: 3 mg/m ³	-
Benzyl alcohol 100-51-6	-	-	TWA: 22 mg/m ³ TWA: 5 ppm Peak: 44 mg/m ³ Peak: 10 ppm Sk*
m-Xylene a,a"-diamine 1477-55-0	-	-	skin sensitizer

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

Peak Limitation - a maximum or peak airborne concentration of a particular substance determined over the shortest analytically practicable period of time which does not exceed 15 minutes.

`Sk' (skin) Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls

Engineering controls

Apply technical measures to comply with the occupational exposure limits. Eyewash stations.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.



Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear suitable protective clothing. Boots. Overalls.

Hand protection

Wear suitable gloves. Impervious gloves.

Respiratory protection

If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Environmental exposure controls

No information available.

Thermal hazards

No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	No information available
Color	Amber
Odor	Aromatic
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	> 94°C	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	
Vapor density	No data available	
Relative density	1.47	
Water solubility	No data available	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information**Section 10: Stability and reactivity**Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials Strong oxidizing agents. Strong acids.

Hazardous decomposition products

Hazardous decomposition products Carbon oxides. Oxides of silicon. Oxides of magnesium. Nitrogen oxides.

Section 11: Toxicological informationInformation on likely routes of exposure

Product Information No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:

Inhalation May cause irritation.

Eye contact Severely irritating to eyes. Causes burns.

Skin contact Irritating to skin. May cause sensitization by skin contact.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms May cause redness and tearing of the eyes.

Acute toxicity .**Numerical measures of toxicity - Product Information**

No information available

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Cashew nutshell liquid	> 1000 mg/kg (Rat)	> 2000 mg/kg (Rat)	-
Benzyl alcohol	= 1230 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 4178 mg/m ³ (Rat) 4 h
m-Xylene a,a"-diamine	= 660 mg/kg (Rat)	= 2 g/kg (Rabbit)	= 1.38 mg/L (Rat) 4 h = 1.16 mg/L (Rat) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin. Classification is based on mixture calculation methods based on component data.

Serious eye damage/eye irritation Risk of serious damage to eyes. Classification is based on mixture calculation methods based on component data.

Respiratory or skin sensitization May cause sensitization by skin contact. Classification is based on mixture calculation methods based on component data.

Germ cell mutagenicity No information available.

Carcinogenicity Based on available data, the classification criteria are not met.

Chemical name	Australia	European Union	IARC
Talc - 14807-96-6	-	-	Group 3

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

Chronic effects: Talc (not containing asbestos or asbestiform fibres) has been classified by the International Agency for Research on Cancer (IARC) as a Group 3 agent. The agent is not classifiable as to its carcinogenicity to humans.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity Keep out of waterways.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Talc	-	LC50: >100g/L (96h, Brachydanio rerio)	-	-
Benzyl alcohol	-	LC50: =460mg/L (96h, Pimephales promelas) LC50: =10mg/L (96h, Lepomis macrochirus)	-	EC50: =23mg/L (48h, water flea)
m-Xylene a,a"-diamine	-	LC50: =87.6mg/L (96h, Oryzias latipes)	-	-

Terrestrial ecotoxicity There is no data for this product.

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Cashew nutshell liquid	6.7
Benzyl alcohol	1.05
m-Xylene a,a"-diamine	0.18

Mobility

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Waste treatment methods**Waste from residues/unused products**

Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation. Should not be released into the environment.

Contaminated packaging

Dispose of contents/containers in accordance with local regulations. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

See section 8 for more information

Section 14: Transport information**ADG**

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

IATA

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

IMDG

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Section 15: Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations****Australia**

Classified as a hazardous substance in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS). Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Australian Industrial Chemicals Introduction Scheme (AICIS)

-

Chemical name	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Talc - 14807-96-6	Present	-
Cashew nutshell liquid - 8007-24-7	Present	-
Benzyl alcohol - 100-51-6	Present	-
m-Xylene a,a"-diamine - 1477-55-0	Present	-

Illicit Drug Precursors/Reagents

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Benzyl alcohol - 100-51-6	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories

AIIC	All the constituents of this material are listed on the Australian Inventory of Industrial Chemicals.
NZIoC	Contact supplier for inventory compliance status.
TSCA	Contact supplier for inventory compliance status.
DSL/NDSL	Contact supplier for inventory compliance status.
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
IECSC	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.

Legend:**AIIC- Australian Inventory of Industrial Chemicals****NZIoC - New Zealand Inventory of Chemicals****TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS** - Japan Existing and New Chemical Substances**IECSC** - China Inventory of Existing Chemical Substances**KECL** - Korean Existing and Evaluated Chemical Substances**PICCS** - Philippines Inventory of Chemicals and Chemical Substances**International Regulations****The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable**The Stockholm Convention on Persistent Organic Pollutants** Not applicable**The Rotterdam Convention** Not applicable**Section 16: Other information****Reason(s) For Issue:** 5 Yearly Revised Primary SDS**Prepared By** This Safety Data Sheet has been prepared by IXOM Operations Pty Ltd (Toxicology and SDS Services).**Revision date:** 25-Nov-2024**Revision Note:**

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Section 1 - Emergency Telephone Number updated

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
 PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
 vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
 STOT: Specific Target Organ Toxicity
 ATE: Acute Toxicity Estimate
 LC50: 50% Lethal Concentration
 LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
 U.S. Environmental Protection Agency ChemView Database
 European Food Safety Authority (EFSA)
 Environmental Protection Agency
 Acute Exposure Guideline Level(s) (AEGl(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 National Institute of Technology and Evaluation (NITE)
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
 Australian Industrial Chemicals Introduction Scheme (AICIS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 U.S. National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program
 Organization for Economic Co-operation and Development Screening Information Data Set
 World Health Organization

Disclaimer

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Liquimix Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Liquimix representative or Liquimix Pty Ltd at the contact details on page 1.

Liquimix Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

End of Safety Data Sheet