

SAFETY DATA SHEET



Revision date: 19-May-2022

Revision Number 2

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product identifier

Product Name Civilox – PW300 Part B

Product Code(s) 000000067034

Other means of identification

Synonyms SDS004/01

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Concrete sealer.

Uses advised against No information available.

Supplier

Liquimix Pty Ltd
ABN: 32 062 887 585
Street Address: 24 Rosa Place
Richlands QLD 4077
Australia

Telephone Number: +61 7 3277 6655

*Emergency telephone number

Emergency telephone number **1800 638 556 (24 HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

GHS Classification

Not classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG)

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 2

SIGNAL WORD

Warning

Label elements

Exclamation mark
Health hazard

**Hazard statements**

H315 - Causes skin irritation

H341 - Suspected of causing genetic defects

Precautionary Statements - Prevention

Obtain special instructions before use

Wear protective gloves / protective clothing / eye protection / face protection

Do not handle until all safety precautions have been read and understood

Wash face, hands and any exposed skin thoroughly after handling

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention if you feel unwell

IF ON SKIN: Wash with plenty of soap and water

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

Poisons Schedule (SUSMP) 5

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Cashew nutshell liquid	8007-24-7	60-90%
2,4,6-Tri(dimethylaminomethyl)phenol	90-72-2	<10%
m-Xylene a,a"-diamine	1477-55-0	<10%
Ethylene diamine	107-15-3	<1%
Phenol	108-95-2	<2%
Non-hazardous ingredients	Proprietary	Balance

4. FIRST AID MEASURES**Description of first aid measures****General advice**

For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor.

Inhalation

Remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms occur.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Get medical attention if irritation develops and persists.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes, and clothing.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Suitable Extinguishing Media Dry chemical, CO2, water spray or regular foam.

Unsuitable extinguishing media

Specific hazards arising from the chemical

Specific hazards arising from the chemical In the event of fire, cool tanks with water spray.

Hazardous combustion products Carbon oxides. Oxides of silicon. Oxides of magnesium. Nitrogen oxides.

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes, and clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal.

Methods for cleaning up

Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

7. HANDLING AND STORAGE**Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Avoid breathing vapors or mists. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes, and clothing.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes, and clothing. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use.

Incompatible materials

Strong oxidizing agents.

Poisons Schedule (SUSMP)

5

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure Limits**

No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Chemical name	Australia	ACGIH TLV
m-Xylene a,a'-diamine 1477-55-0	0.1 mg/m ³ Peak	S* Ceiling: 0.018 ppm
Ethylene diamine 107-15-3	10 ppm 25 mg/m ³	TWA: 10 ppm S*

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

Peak Limitation - a maximum or peak airborne concentration of a particular substance determined over the shortest analytically practicable period of time which does not exceed 15 minutes.

`Sk' (skin) Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls**Engineering controls**

Apply technical measures to comply with the occupational exposure limits. Eyewash stations.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear suitable protective clothing. Boots. Overalls.

Hand protection

Wear suitable gloves. Impervious gloves.

Respiratory protection

If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Environmental exposure controls

No information available.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Liquid
Appearance	No information available.
Color	Amber
Odor	Aromatic
Odor threshold	No information available.

Property	Values	Remarks • Method
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	101°C	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	

Vapor pressure	No data available	
Vapor density	No data available	
Relative density	1.04	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information**10. STABILITY AND REACTIVITY**Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Carbon oxides. Oxides of silicon. Nitrogen oxides.

11. TOXICOLOGICAL INFORMATIONAcute toxicityInformation on likely routes of exposure

Product Information No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:

Inhalation May cause irritation.

Eye contact May cause irritation.

Skin contact Irritating to skin.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms No information available.

Numerical measures of toxicity - Product Information

No information available.

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Cashew nutshell liquid	> 1000 mg/kg (Rat)	-	-
2,4,6-Tri(dimethylaminomethyl)phenol	= 1200 mg/kg (Rat)	= 1280 mg/kg (Rat)	-
m-Xylene a,a"-diamine	= 660 mg/kg (Rat)	= 2 g/kg (Rabbit)	= 700 ppm (Rat) 1 h
Ethylene diamine	= 637 mg/kg (Rat)	= 560 mg/kg (Rabbit)	4916 - 9832 mg/m ³ (Rat) 8 h
Phenol	= 340 mg/kg (Rat) = 317 mg/kg (Rat)	= 630 mg/kg (Rabbit)	= 316 mg/m ³ (Rat) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin. Classification is based on mixture calculation methods based on component data.

Serious eye damage/eye irritation Risk of serious damage to eyes. Classification is based on mixture calculation methods based on component data.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Reproductive toxicity May cause heritable genetic damage. Classification is based on mixture calculation methods based on component data.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity Keep out of waterways.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
m-Xylene a,a"-diamine	-	LC50: =87.6mg/L (96h, Oryzias latipes)	-	-

Ethylene diamine	EC50: =645mg/L (72h, Pseudokirchneriella subcapitata) EC50: =151mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 98.6 - 131.6mg/L (96h, Pimephales promelas) LC50: 191 - 254mg/L (96h, Pimephales promelas) LC50: =115.7mg/L (96h, Pimephales promelas) LC50: 180 - 560mg/L (96h, Poecilia reticulata)	-	EC50: =17mg/L (48h, Daphnia magna)
Phenol	EC50: =46.42mg/L (96h, Pseudokirchneriella subcapitata) EC50: 0.0188 - 0.1044mg/L (96h, Pseudokirchneriella subcapitata) EC50: 187 - 279mg/L (72h, Desmodesmus subspicatus)	LC50: 11.9 - 50.5mg/L (96h, Pimephales promelas) LC50: 20.5 - 25.6mg/L (96h, Pimephales promelas) LC50: =32mg/L (96h, Pimephales promelas) LC50: 5.449 - 6.789mg/L (96h, Oncorhynchus mykiss) LC50: 7.5 - 14mg/L (96h, Oncorhynchus mykiss) LC50: 4.23 - 7.49mg/L (96h, Oncorhynchus mykiss) LC50: =27.8mg/L (96h, Brachydanio rerio) LC50: =0.00175mg/L (96h, Cyprinus carpio) LC50: 33.9 - 43.3mg/L (96h, Oryzias latipes) LC50: 23.4 - 36.6mg/L (96h, Oryzias latipes) LC50: 5.0 - 12.0mg/L (96h, Oncorhynchus mykiss) LC50: =13.5mg/L (96h, Lepomis macrochirus) LC50: 11.9 - 25.3mg/L (96h, Lepomis macrochirus) LC50: =11.5mg/L (96h, Lepomis macrochirus) LC50: 34.09 - 47.64mg/L (96h, Poecilia reticulata) LC50: =31mg/L (96h, Poecilia reticulata)	-	EC50: 4.24 - 10.7mg/L (48h, Daphnia magna) EC50: 10.2 - 15.5mg/L (48h, Daphnia magna)

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation No information available.

Component Information

Chemical name	Partition coefficient
Ethylene diamine	-1.221
Phenol	1.5

Mobility

Mobility in soil No information available.

Other adverse effects

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

14. TRANSPORT INFORMATION

ADG

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

IATA

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

IMDG

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

Not classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG)

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

Poisons Schedule (SUSMP) 5

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Ethylene diamine - 107-15-3	20 MWH Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

Phenol - 108-95-2

10 tonne/yr Threshold category 1

International Inventories**AIIC**

All the constituents of this material are either listed on the Australian Inventory of Industrial Chemicals or have been assessed under the National Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Legend:

- Australian Inventory of Industrial Chemicals

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

16. OTHER INFORMATION

Reason(s) For Issue: Revised Primary SDS
Change in Formulation

Issuing Date: 19-May-2022

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

Revision Note:

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Section 1 - Emergency Telephone Number updated

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australian Industrial Chemicals Introduction Scheme (AICIS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
RTECS (Registry of Toxic Effects of Chemical Substances)
World Health Organization

Disclaimer

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Liquimix Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Liquimix representative or Liquimix Pty Ltd at the contact details on page 1.

Liquimix Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

End of Safety Data Sheet