

# LM Non-Slip-20

## PRODUCT

### DESCRIPTION

Extra coarse particle size grades of micronised polypropylene are used for adding texture, structure, and non-slip properties to a wide variety of paints and coatings.

## INTENDED

### USES

- Anti-Slip Additive for Topcoat

## FEATURES

- Coarse textured coating surface
- Excellent Durability
- Ideal for Non-Slip purposes
- Easy to disperse with high speed mixing

## PRODUCT DATA

<b>Finish</b>	Anti-Slip Finish
<b>Colour</b>	White
<b>Typical Thickness</b>	1500 Microns Dry Film Thickness
<b>Maximum Particle Size</b>	< 841 $\mu\text{m}$ (20 mesh)
<b>Flash Point</b>	> 277 °C
<b>Melting Point</b>	166 - 168 °C
<b>Specific Gravity</b>	0.90 @ 25°C

## APPLICATION

### Mixing

Recommended Addition Levels: 3.0 - 10.0%

## COMPATIBILITY

### Topcoats

Aralox-FL170  
Opalon-F45  
Opalon-S30

## STORAGE &

### HANDLING

Store in dry, shaded conditions away from sources of heat and in the original properly sealed containers. Protect from heat and frost. Protect contents from moisture.

## PACK SIZE

1Kg Kits  
1Kg of LM Non-Slip-20 in a 2L Container

## DISCLAIMER

The information contained herein is offered without charge and is for use by technically qualified personnel at their own risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and no warranty of any kind is made with respect thereto.