

LM Non-Slip 50S

Course Textured Grade

PRODUCT

DESCRIPTION Extra coarse particle size grades of micronised polypropylene are used for adding texture, structure, and non-slip properties to a wide variety of paints and coatings.

INTENDED

USES

- Anti-Slip Additive for Topcoat

FEATURES

- Course textured coating surface
- Excellent Durability
- Ideal for Non-Slip purposes
- Easy to disperse with high-speed mixing

PRODUCT DATA

Finish	Anti-Slip Finish
Colour	White
Maximum Particle Size	< 297 μm (50 mesh)
Mean Particle Size	80 - 100 μm
Flash Point	> 277 °C
Melting Point	166 - 168 °C
Specific Gravity	0.90 g/cc

APPLICATION

Mixing

Recommended Addition Levels: 3.0 - 10.0%

COMPATIBILITY

Topcoats	Aralox-FL170 Opalon-F45 Opalon-S30
-----------------	--

STORAGE & HANDLING

Store in dry, shaded conditions away from sources of heat and in the original properly sealed containers. Protect from heat and frost. Protect contents from moisture.

PACK SIZE

1Kg Kits
1Kg of LM Non-Slip 50S in a 2L Container

DISCLAIMER

The information contained herein is offered without charge and is for use by technically qualified personnel at their own risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and no warranty of any kind is made with respect thereto.

LiquiMix Pty Ltd - ABN 32 062 887 585
24 Rosa Place, Richlands QLD 4077
Phone: 1300 123 085

Web: - www.liquimix.com
Sales Enquiries: - sales@liquimix.com
Account Enquiries: - accounts@liquimix.com